

technical data sheet

BOSTIK 1465

Solvent Based Air Conditioning Duct Sealant

PRODUCT

Bostik 1465 Duct Sealant is a one part solvent based sealing compound.

DESCRIPTION

Bostik 1465 Duct Sealant is a fire rated product supplied in 300ml cartridges for sealing high velocity air conditioning ductwork.

RECOMMENDED USES

- General air conditioning and ductwork sealing
- Sealing metal sheeting
- Suitable for heating/cooling application
- High velocity duct work
- Use in truck and trailer sealing
- Setting and sealing aluminium window frames

FEATURES & BENEFITS

- Fire-rated
- Fast setting/drying (within 30 minutes)
- Excellent adhesive to most materials
- Very long lasting
- Internal/external applications
- Flexible
- Paintable
- Completely weatherproof when cured
- Good chemical resistance

PERFORMANCE PROPERTIES

TEST	RESULT
Colour	Grey
Type	Neoprene Rubber/Resin
Temperature Range	-20°C to +100°C
Solids Content	65%
S.G.	1.20

RATED 0,0,0,0-1 for early fire hazard properties to AS 1530.3 (1982)

PACKAGING

Bostik 1465 is available in 300ml cartridges packed 20 per carton.

COVERAGE

15 lineal metres per 5mm bead.

APPLICATION INSTRUCTIONS

- All surfaces must be clean and in good condition
- Use with standard cartridge type (skeleton) gun.

PRECAUTIONS

- If using in exterior applications, sealant must be painted over after 1 hour with a suitable oil based paint
- Use in well ventilated areas as product is solvent based

P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

HEALTH AND SAFETY

On contact, uncured sealant causes irritation. Gloves and protective goggles must be worn during application and use.

- Avoid contact with skin, eyes and avoid breathing in vapour.
- Wear protective gloves when mixing or using
- If poisoning occurs, contact a doctor or Poisons Information Centre.
- If swallowed, do not induce vomiting. Give a glass of water.
- If skin contact occurs, remove contaminated clothing and wash skin thoroughly for a minimum of 15 minutes and see a doctor.
- For more detailed information refer to Material Safety Data Sheet.

CLEAN-UP

Use **Bostik 9913** solvent or mineral turps

STORAGE/SHELF LIFE

Minimum of 12 months if stored between 5°C to 25°C under cover in original unopened containers.

FIRE

Product is highly flammable, store away from heat sources.

BOSTIK 1465

ITEM NO.	STOCK SIZE
098965	Bostik 1465 Duct Sealant 320gm

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Findley Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK FINDLEY AUSTRALIA PTY LTD

FOR FURTHER INFORMATION



BOSTIK FINDLEY AUSTRALIA PTY LTD
 Phone: +61-3-9279 9333
 Fax: +61-3-9279 9240

BOSTIK FINDLEY NZ LIMITED
 Phone: +64-4-567 5119
 Fax: +64-4-567-5412

BOSTIK FINDLEY SINGAPORE PTE LTD
 Phone: +65-863 4088
 Fax: +65-863 4077

BOSTIK FINDLEY (MALAYSIA) SDN BHD
 Phone: +606 764 3246
 Fax: +606 764 3248

SYDNEY
 Phone: 02 8825 3488
 Fax: 02 8825 3411

ADELAIDE
 Phone: 08 8244 0511
 Fax: 08 8244 0522

PERTH
 Phone: 08 9331 7666
 Fax: 08 9331 7677

BRISBANE
 Phone: 07 3265 2377
 Fax: 07 3265 5421

(ABN 79 003 893 838)

Product: Bostik 1465
 Issue Date: March 2002
 Issue No: 1
 Division: Industrial
 Total Pages: 1